LISTING OF CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application.

- 1-13. (Canceled)
- 14. (Currently amended) A composite material fabricated by a process comprising:
- a) forming a fibrous structure comprising carbon, polyacrylonitrile, <u>or rayon er</u> eeramic fibers into a preform;
- b) initially predominantly coating the fibers of that fibrous structure preform with elemental carbon to impregnate that preform with elemental carbon;
- c) infiltrating the preform with a ceramic slurry to predominantly impregnate the fibers of the preform to form an impregnated green body;
- d) infiltrating the impregnated green body with a liquid carbon precursor and pyrolyzing the <u>liquid</u> carbon <u>precursor</u> to form a carbon char;
- e) infiltrating the impregnated green body with molten silicon to form a continuous matrix throughout the composite; and
- f) reacting silicon in the continuous matrix with the carbon char to form silicon carbide.
- 15. (Original) The composite of claim 14, wherein the ceramic slurry is a boron carbide slurry.
- 16. (Original) The composite of claim 14, wherein said fibers of said preform are made from polyacrylonitrile.

- 17. (Canceled)
- 18. (Original) The composite of claim 14, wherein said liquid carbon precursor is liquid naphthalene.
- 19. (Original) The composite of claim 14, wherein said molten silicon is a non alloyed silicon.
- 20. (Original) The composite of claim 14, wherein said molten silicon is an alloyed silicon.
- 21. (Original) The composite of claim 14, wherein said fibrous structure is initially coated with chemically vapor deposited elemental carbon.
- 22. (Original) The composite of claim 14, wherein said elemental carbon is deposited on the fibers using pitch or resin.
- 23. (Original) The composite of claim 14, wherein said infiltration with molten silicon occurs in the temperature range of about 1425 to about 1485° C.
- 24. (Original) The composite of claim 15, wherein said boron carbide slurry comprises boron carbide having a particle size of less than about 1 micron.
 - 25. (Currently amended) A composite ceramic material comprising:
- a.) a fibrous structure comprising carbon, polyacrylonitrile, <u>or</u> rayon er eeramic fibers and a silicon matrix which are initially predominantly impregnated with elemental carbon, and subsequently predominantly impregnated with boron carbide; and
- b.) a silicon carbide phase which is continuous and predominantly encompasses said fibrous structure, wherein silicon carbide in said silicon carbide phase has a grain size of less than about 10 microns.

26-32. (Canceled)

- 33. (Original) A composite ceramic material according to claim 25, wherein the amount of unreacted silicon in the matrix is less than that required to form a liquid phase on the wear face of a disk made from the composite material during a severe energy event.
- 34. (Original) A composite ceramic material according to claim 25, wherein said composite material exhibits an absence of large SiC grains.
- 35. (Original) A composite ceramic material according to claim 34, wherein said large grains are larger than about 20 microns.
- 36. (Original) A composite ceramic material according to claim 25, wherein said material is less than 5 volume % residual silicon.
- 37. (Original) A composite ceramic material according to claim 25, wherein said boron carbide comprises about 5 to about 15 volume % of said material.
- 38. (Original) A composite ceramic material according to claim 25, wherein said fibrous structure impregnated with elemental carbon comprises from about 20 to about 45 volume % of said material.
- 39. (Original) A composite ceramic material according to claim 25, wherein said silicon carbide phase comprises from about 20 to about 40 volume % of said material.
- 40. (Original) A composite ceramic material according to claim 25, wherein said boron carbide has an average particle size of less than about 1 micron.
 - 41. (Canceled)

- 42. (Original) A composite ceramic material according to claim 25, wherein said fibrous structure comprises from about 15 to about 40 volume % of said material.
 - 43. (Currently amended) A composite ceramic material comprising:
- a.) a fibrous structure and a silicon matrix which are initially predominantly impregnated with elemental carbon, and subsequently predominantly impregnated with boron carbide; and
- b.) a silicon carbide phase which is continuous and predominantly encompasses said fibrous structure, wherein silicon carbide in said silicon carbide phase has a grain size of less than about 10 microns, whenever said fibrous structure comprises carbon polyacrylonitrile, or rayon or ceramic fibers or combinations thereof.